Data Sheet

We make sure



Issue: February 2009

LIFEBOOK S6420 Get ready for your next business trip

Fujitsu Siemens Computers is the leading European IT manufacturer. With a strategic focus on innovative mobility and the dynamic data center, we offer a unique range of products and services from notebooks and desktops to servers and IT infrastructure solutions. Famous German engineering and exceptional in-house quality testing capabilities in our test centers ensure extraordinary product quality and reliability across all product lines.

LIFEBOOK S6420

The LIFEBOOK S6420 is ideal for all business trips with its fantastic performance and genuine mobility. Weighing only 1.6 kg and together with its 13.3" WXGA display and long battery life, it is easy to use all day long. The new integrated application buttons guarantee fast access to your personal applications. Integrated 3G/UMTS and a built-in ConfCamera ensure trouble-free wireless connectivity.

Slim mobility

Enjoy easy access to all your data thanks to a mobile device that is both lightweight and versatile.

 A slim and lightweight (1.7 kg) notebook with a 13.3-inch WXGA display that can run up to 11 hours with a second battery

Maximum connectivity

Available everywhere: wireless connectivity anytime, anywhere even if there is no hotspot nearby.

■ Optional integrated 3G/UMTS, WLAN and Bluetooth

Reliable companion

Secure and effective working even for the most demanding of users in all situations.

Spill-proof keyboard, shock sensor, magnesium lid and further innovative highlights

Flexible working

Adapt your notebook to various business environments and thus increase your business agility.

■ Modular bay for a second battery or an optical drive

Maximum security

Protect your company data against unauthorized third-party access and benefit from our end-to-end anti-theft and system protection concept.

Fingerprint sensor, TPM module and SmartCase Logon+































Components	
Processor	Intel® Core™2 Duo T9600 (2.8 GHz, 6 MB, 1066 MHz)
	Intel® Core™2 Duo T9550 (2.66 GHz, 6 MB, 1066 MHz)
	Intel® Core™2 Duo T9400 (2.53 GHz, 6 MB, 1066 MHz)
	Intel® Core™2 Duo P8700 (2.53 GHz, 3 MB, 1066 MHz) Intel® Core™2 Duo P8600 (2.4 GHz, 3 MB, 1066 MHz)
	Intel® Core™2 Duo P8400 (2.26 GHz, 3 MB, 1066 MHz)
Memory modules	2 GB (1 module(s) with 2 GB, DDR3), 1066 MHz 1 GB (1 module(s) with 1 GB, DDR3), 1066 MHz
Hard disk drives (internal)	320 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
Talu di Gioria di Tropi (internal)	160 GB, 7200 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T.
	160 GB, 5400 rpm, FDE-3, 2.5-inch S.M.A.R.T.
	120 GB, 5400 rpm, SATA, 2.5-inch S.M.A.R.T. 64 GB SSD SATA, 2.5-inch
Hard disk notes	ShockSensor for HDD shock protection
	One Gigabyte equals one billion bytes, when referring to hard disk drive capacity. Accessible capacity may vary, also depending on used software and tool
WLAN (optional)	Atheros Minicard b/g 802.11 b/g Intel® Wireless WiFi Link 5300 AGN 11/13ch
UMTS/HSUPA (optional)	Sierra Wireless MC8790 (downlink 7.2 MBit/s, uplink 2.0 MBit/s)
Modular bay options	2nd battery
	DVD Super Multi
	Weight saver
Base unit	LIFEBOOK S6420, 13.3-inch WXGA
General system information	Intel® OME TOUR M
Chipset BIOS features	Intel® GM45, ICH 9-M BIOS Flash EPROM
Biod icatales	BIOS based on Phoenix TrustedCore Notebook
Memory slots	2 DIMM
Turbo memory	Optional 4 GB
Supported capacity RAM (max.)	4 GB
Memory notes	DDR3 - 1066 MHz 8 GB - with future memory models.
Interfaces	
Memory card slots	1
PC Card slot (Type I/II)	1
SIM card slot Modem (RJ-11)	1
USB 2.0 total	3
S-Video out (TV-out)	1
FireWire (IEEE1394)	1
VGA	1
Ethernet (RJ-45)	1
DC-in	1
Audio: line-in / microphone Audio: line-out / headphone	1
Internal microphones	2
Docking connector for Port Replicator	1
Kensington Lock support	1
Wired communication Modem type	56 K V.92 modem MDC1.5
LAN	Built-in 10/100/1000 MBit/s Marvell 88E8055
Wireless technologies	
Antennas	3 Dual band WLAN antennas, 2 UMTS antennas
Infrared link (Fast IrDa 1.1, 4 Mbps) WLAN notes	Import and usage according to country-specific regulations.
Keyboard and pointing devices	
•	Spill-proof keyboard
	Number of keyboard keys: 85, Keyboard pitch: 19 mm, Keyboard stroke: 3 mm
	Fingerprint sensor
	Launch keys Application buttons
	LockWorkstation button
	MobilityCenter button
	EcoButton
	Status LED

Multimedia Audio type On board Realtek ALC269 Audio codec

Multimedia

Audio features Stereo speakers, 2 internal microphones Camera Built-in ConfCamera, 1.3 megapixel, VGA camera

Graphics

Display 13.3-inch TFT 1280 x 800 pixel (WXGA) LED glare display

max. resolution external display 1920 x 1200 / true color / 60 Hz Graphics brand name Mobile Intel® GMA 4500M HD

Graphic features DualView (Windows XP & Windows Vista)

Power supply

AC adapter 19 V / 80 W (4.22 A) Rated voltage range 100 - 240 V (AC Input)

Rated frequency range 50 - 60 Hz

1st battery 1st Li-Ion battery 6-cell, 5800 mAh, 62 Wh

2nd Li-Ion battery 6 cell (Option), 2500 mAh, 25.3 Wh 2nd battery

Battery features Dynamic charge supported (rapid charge)

Benchmark Mobile Mark 2005

5 h (Mobile Mark 2005 reader workload) Runtime 1st battery Runtime 1st + 2nd battery 8.5 h (Mobile Mark 2005 reader workload)

Disclaimer: Battery life may vary depending on product model, configuration, applications, power management Battery notes

settings and features utilized. Battery recharge time depends on usage.

Power consumption

Power consumption note see white paper Energy Consumption

Link to Energy White Paper http://docs.fujitsu-siemens.com/dl.aspx?id=5b4ac52e-8324-4683-b833-492c5e3c3e11

Dimensions / Weight / Environmental

Dimension (W x D x H) 314 x 234 x 22.4 - 33.5 mm

Weight 1.7 kg

Weight notes Weight may vary depending on actual configuration.

Operating ambient temperature 5 - 35°C

Operating relative humidity 20 - 85 % (running)

Operating system

Operating system optional preinstalled Microsoft® Windows Vista® Business 32bit

Microsoft® Windows Vista® Home Basic

TwinLoad Microsoft® Windows® XP Professional (DVD)

Microsoft® Windows® XP Professional Operating system compatible

Operating system notes Driver support for Microsoft Windows XP Professional

Additional Software

Additional software (preinstalled) Adobe Acrobat Reader

Application Panel Display Manager ShockSensor Utility Power Saving Utility Wireless Selector Utility

EasyGuide online user documentation Nero Essentials S (CD / DVD write software)

Norton Internet Security (incl. Firewall) on Drivers & Utilities DVD for Microsoft Windows XP

Toshiba Stack 4.x

Windows Vista® recovery media Additional software (optional)

Drivers & Utilities DVD (DUDVD)

UMTS connection manager (optional with UMTS)

DVD playback software

Additional software (included as a

CD/DVD)

SmartCase Logon+

Manageability Manageability features DeskUpdate Driver management

DeskView Migrate (optional) DeskView Control (optional)

DeskView 10.x client management including: Manageability type DeskView features

On/Offline remote client management

Detailed system inventory management and reports **BIOS Management**

Remote power management System notifications Security Remote Control DeskView Helpdesk Integration WoL (Wake on LAN)

WMI

Supported standards

PXE

BootP (made4you)

Manageability link http://www.fujitsu-siemens.com/solutions/it infrastructure solutions/manageability/featurefinder.html

Security

Physical security Kensington Lock support

Optional: Trusted plattform module (TPM 1.2) System security

Symantec Norton Internet Security (90 day test version)

Security

User security Integrated Fingerprint Sensor

Integrated SmartCard controller in PC Card with system lock support

Hard disk password

SystemLock BIOS SmartCard security SmartCase Logon+ incl. Fingerprint software User and supervisor BIOS password

Compliance

CE Europe

CE!

USA/Canada FCC Class B (Depending on wireless configuration)

> cUL UL

Global RoHS (Restriction of hazardous substances)

WEEE (Waste electrical and electronical equipment) Microsoft Operating Systems (HCT / HCL entry / WHQL)

WiFi certified Energy Star 4.0 EPEAT Silver

Compliant with ISO13406-2 (Pixel fault class II)

https://sp.fujitsu-siemens.com/sites/certificates/default.aspx Compliance link

Portreplicator interfaces (optional)

DC-in 1 Power on switch 1 Headphones 1 Audio: microphone in 1 USB 2.0 total VGA

DVI 1 (with HDCP Support)

Serial (RS-232) Mouse / Keyboard (PS/2) Ethernet (RJ-45) Parallel 1 Kensington Lock support 2

Possible Accessories

Accessories included Exclusive pouch

Warranty

Standard Warranty 2 years

Service level Collect & Return Service / Bring-In Service (depending on country)

Maintenance and Support Services - the perfect extension Recommended Service 3 years, On-site Service

Spare Parts availability 5 years

Service Weblink www.fujitsu-siemens.com/Supportservice



Information about environmental care, policies, programs and our Environmental Guideline FSC

http://www.fujitsu-siemens.com/aboutus Take back and Recycling information: http://www.fujitsu-siemens.com/recycling

All rights reserved, including intellectual property rights. Technical data subject to modifications and delivery subject to availability. Any liability that the data and illustrations are

complete, actual or correct is excluded.

Designations may be trademarks and/or copyrights of the respective manufacturer, the use of which by third parties for their own purposes may infringe the rights of such owner. For further information see http://www.fujitsu-siemens.com/terms_of_use.html

Copyright © Fujitsu Siemens Computers February 2009 Published by
Fujitsu Siemens Computers

http://www.fujitsu-siemens.com/